

## LANCOM OAP-821

**Single-radio outdoor 11ac WLAN access point for professional outdoor WLAN applications – either in the 2.4-GHz or 5-GHz frequency band**



The LANCOM OAP-821 is ideal for the reliable wireless coverage of open spaces either in the 2.4-GHz or 5-GHz frequency band. Thanks to the integrated 5-GHz antenna it is also suitable for high-speed point-to-point connections for a wireless networking buildings.

- Single operation WLAN – operation at 2.4 or 5 GHz with up to 300 Mbps with IEEE 802.11n and 867 Mbps with IEEE 802.11ac
- Integrated 5-GHz directional antenna and external antenna connectors also for 2.4 GHz
- Robust IP66 protective housing – reliable even at extreme temperatures (-33°C to +70°C)
- Dynamic WLAN optimization thanks to LANCOM Active Radio Control (ARC)
- Professional security features such as IEEE 802.1X
- IPSec-VPN support with LANCOM OAP VPN Option
- Operation via LANCOM Management Cloud, WLAN controller or stand-alone
- Connector for Gigabit Ethernet with Power over Ethernet as per IEEE 802.3af

LCOS 10.50

# LANCOM OAP-821

## **Single Operation Wi-Fi with up to 867 Mbps**

The LANCOM OAP-821 provides either reliable WLAN coverage in the 2.4-GHz frequency band or high-speed P2P links for connecting remote buildings in the 5-GHz band with up to 250 Mbps.

## **Maximum reliability in all weathers**

The LANCOM OAP-821 has a rugged IP-66 protective housing, making it fully dust proof and water-jet resistant. It withstands temperatures between -33°C and +70°C to guarantee reliable operations even under extreme conditions.

## **Wireless freedom**

The LANCOM OAP-821 supports IEEE 802.11ac for highly powerful point-to-point links for the interconnection of separate buildings. Setting up a wireless network of this type spares you the need for laborious cable installations and expensive leased lines.

## **Active Radio Control for dynamic radio-field optimization**

The LANCOM OAP-821 supports the WLAN optimization concept LANCOM Active Radio Control. This intelligent combination of innovative features included with the LCOS operating system - such as Adaptive Noise Immunity, Adaptive RF Optimization or Client Steering - sustainably increases WLAN performance and supports administrators with professional tools for WLAN management.

## **LANCOM security for wireless networks**

With numerous integrated security features, such as IEEE 802.1X, this outdoor access point provides optimal security for networks. Administrators and employees alike benefit from professional security policies on the network.

## **Optional VPN functionality**

The LANCOM OAP VPN Option upgrades the outdoor access points of the OAP-8xx series with VPN functionality. This way, maintenance and management can be conducted remotely via an encrypted IPSec VPN tunnel. Furthermore, a trusted WLAN can be provided via a securely encrypted VPN tunnel to the company headquarters.

## **Zero-touch deployment**

The LANCOM OAP-821 can be versatilely operated: Managed via the LANCOM Management Cloud it is integrated into a comprehensive, automated network orchestration, based on Software-defined Networking technology. It can also be operated via a LANCOM WLAN controller or be applied in stand-alone operation.

# LANCOM OAP-821

**Maximum future viability**

The LANCOM OAP-821 supports the high-speed WLAN standard IEEE 802.11ac, so that you are well equipped for future challenges. LANCOM products are designed for a service life of several years and are equipped with hardware dimensioned for the future. Even reaching back to older product generations, updates to the LANCOM Operating System - LCOS - are available several times a year, free of charge and offering major features.

# LANCOM OAP-821

## WLAN product specifications

Frequency band 2.4 GHz or 5 GHz	2400-2483.5 MHz (ISM) or 5180-5700 MHz (depending on country-specific restrictions)
Integrated Antenna Gain	up to 18 dBi in 5 GHz possible with the integrated dual polarisation antenna
HPBW	5 GHz: 16° horizontal, 16° vertikal
Data rates IEEE 802.11ac/n	867 Mbps according to IEEE 802.11ac with MCS9 (fallback to 6,5 Mbps with MCS0). Compatible to IEEE 802.11ac/n/a, IEEE 802.11 ac/n, IEEE 802.11n/a compatibility mode or pure IEEE 802.11ac, pure IEEE 802.11n, pure IEEE 802.11a mode and data rates selectable
Data rates IEEE 802.11n	300 Mbps according to IEEE 802.11n with MCS15 (fallback to 6,5 Mbps with MCS0). Compatible to IEEE 802.11a/n, IEEE 802.11g/n, IEEE 802.11b/g/n or IEEE 802.11b/g compatibility mode or pure IEEE 802.11n, pure IEEE 802.11a, IEEE 802.11g or pure IEEE 802.11b mode and data rates selectable
Data rates IEEE 802.11a/ h	54 Mbps (fallback to 48, 36 , 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection), fully compatible with TPC (adjustable power output) and DFS (automatic channel selection, radar detection) and data rates selectable
Data rates IEEE 802.11b/g	54 Mbps to IEEE 802.11g (fallback to 48, 36, 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection) compatible to IEEE 802.11b (11, 5.5, 2, 1 Mbps, Automatic Rate Selection), IEEE 802.11b/g compatibility mode or pure IEEE 802.11g or pure IEEE 802.11b and data rates selectable
Net Data Throughput	max. 250 Mbps
Range (outdoor / P2P)	The actual range depends on the environmental conditions. The Antenna Distance Calculator on <a href="http://www.lancom-systems.com">www.lancom-systems.com</a> provides information on the possible data rates and distances.
Output power at radio module, 5 GHz and per transmit chain	IEEE 802.11a/h: +17 dBm @ 54 MBit/s; IEEE 802.11an/ac: +16 dBm @ (MCS7, 20 MHz), +15 dBm @ (MCS7, 40 MHz), +15 dBm (MCS9, 20 MHz), +14 dBm (MCS9, 40/80 MHz)
Output power at radio module, 2.4 GHz and per transmit chain	IEEE 802.11b/g: +18 dBm @ 54 MBit/s, IEEE 802.11n: +16 dBm @ (MCS7, 20 MHz), +16 dBm @ (MCS7, 40 MHz)
Max. allowed radiation power (EIRP), 5 GHz	IEEE 802.11a/h: Up to 30 dBm / 1000 mW EIRP (depending on national regulations on channel usage and subject to further obligations such as TPC and DFS)
Max. allowed radiation power (EIRP), 2.4 GHz	IEEE 802.11b/g: Up to 20 dBm / 100 mW EIRP (transmission power control according to TPC)
Minimum transmission power	Transmission power reduction in software in 1 dB steps to min. 0.5 dBm
Receiver sensitivity 5 GHz	IEEE 802.11a/h: -80 dBm @ 54 MBit/s, IEEE 802.11an/ac: -75 dBm @ (MCS7, 20/40MHz), -71 dBm @ (MCS9, 20/40 MHz), -68 dBm (MCS9, 80 MHz)
Receiver sensitivity 2.4 GHz	IEEE 802.11b/g: -80 dBm @ 54 MBit/s, IEEE 802.11n: -77 dBm @ (MCS7, 20 MHz), -75 dBm @ (MCS7, 40 MHz)
Radio channels 5 GHz	Up to 26 non-overlapping channels (available channels and further obligations such as automatic DFS dynamic channel selection depending on national regulations)
Radio channels 2.4 GHz	Up to 13 channels, max. 3 non-overlapping (depending on country-specific restrictions)
Multi-SSID	Up to 15 independent WLAN networks; time-controlled activation and deactivation of WLAN networks

LCOS 10.50

# LANCOM OAP-821

## WLAN product specifications

Concurrent WLAN clients Up to 65 clients (recommended), 128 clients (max.)

## Supported WLAN standards

IEEE standards IEEE 802.11ac (Wi-Fi 5), IEEE 802.11n (Wi-Fi 4), IEEE 802.11a, IEEE 802.11g, IEEE 802.11b, IEEE 802.11i, IEEE 802.1X, IEEE 802.11u, IEEE 802.11r (Fast Roaming), IEEE 802.11w (Protected Management Frames), WME and U-APSD/WMM Power Save as defined in IEEE 802.11e, IEEE 802.11h, IEEE 802.11d

## Standard IEEE 802.11ac (Wi-Fi 5)

Supported features 2x2 MIMO, 80 MHz channels, QAM-256

## Standard IEEE 802.11n (Wi-Fi 4)

Supported features 2x2 MIMO, 40 MHz channel, 20/40MHz coexistence mechanisms in the 2.4 GHz band, MAC aggregation, Block Acknowledgement, STBC (Space Time Block Coding), LDPC (Low Density Parity Check), MRC (Maximal Ratio Combining), Short Guard Interval

## WLAN operating modes

Modes WLAN access point (standalone, WLC or LANCOM Management Cloud managed), WLAN bridge (P2P or P2MP) (standalone or AutoWDS\*), (standalone, WLC or LANCOM Management Cloud managed), WLAN client mode, transparent WLAN client mode

## Security

Encryption options WPA3-Personal, IEEE 802.1X (WPA3-Enterprise, WPA2-Enterprise), IEEE 802.11i (WPA2-Personal), Wi-Fi Certified™ WPA2™, WPA, WEP, IEEE 802.11w (Protected Management Frames), LEPS-MAC (LANCOM Enhanced Passphrase Security MAC), LEPS-U (LANCOM Enhanced Passphrase Security User)

Encryption AES-CCMP AES-GCMP, TKIP, RC4 (only used by WEP)

EAP types (authenticator) EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0/EAP-MSCHAPv2, PEAPv1/EAP-GTC, EAP-FAST

RADIUS/EAP-server User administration MAC-based, rate limiting, passphrases, VLAN user based, authentication of IEEE 802.1X clients via EAP-TLS, EAP-TTLS, EAP-MD5, EAP-GTC, PEAP, MSCHAP, MSCHAPv2, Dynamic Peer Discovery

Others WLAN protocol filters, IP-redirection of any packet received over the WLAN interface, IEEE 802.1X supplicant, background scanning, client detection ("rogue WLAN client detection"), Wireless Intrusion Detection System (WIDS), RADIUS CoA (Change of Authorization)

## LANCOM Active Radio Control

Client Management Steering of WLAN clients to the ideal access point using 802.11k and 802.11v

Managed RF Optimization\* Selection of optimal WLAN channels by the administrator

Adaptive Noise Immunity Better WLAN throughput due to immunity against interferences

Spectral Scan Monitoring your WLAN for sources of interference

LCOS 10.50

# LANCOM OAP-821

## LANCOM Active Radio Control

Adaptive RF Optimization	Dynamic selection of the optimal WLAN channel
Airtime Fairness	Improved utilization of the WLAN bandwidth
Adaptive Transmission Power	Automatic adjustment of the transmission power for Wi - Fi backup scenarios
*) Note	Only in installations with WLAN controller

## Roaming

Roaming	IAPP (Inter Access Point Protocol), IEEE 802.11r (Fast Roaming), OKC (Opportunistic Key Caching), Fast Client Roaming (only in operating mode client modus)
---------	---

## Layer 2 features

VLAN	4.096 IDs based on IEEE 802.1q, dynamic assignment
Quality of Service	WME based on IEEE 802.11e, Wi-Fi Certified™ WMM®
Rate limiting	SSID based, WLAN client based
Multicast	IGMP-Snooping, MLD-Snooping, Multicast-to-Unicast-conversion on WLAN interfaces
Protocols	Ethernet over GRE-Tunnel (EoGRE), ARP-Lookup, LLDP, DHCP option 82, IPv6-Router-Advertisement-Snooping, DHCPv6-Snooping, LDRA (Lightweight DHCPv6 Relay Agent), Spanning Tree, Rapid Spanning Tree, ARP, Proxy ARP, BOOTP, DHCP

## Layer 3 features

Firewall	Stateful inspection firewall including paket filtering, extended port forwarding, N:N IP address mapping, paket tagging, support for DNS targets, user-defined rules and notifications
Quality of Service	Traffic shaping, bandwidth reservation, DiffServ/TOS, packetsize control, layer-2-in-layer-3 tagging
Security	Intrusion Prevention, IP spoofing, access control lists, Denial of Service protection, detailed settings for handling reassembly, session-recovery, PING, stealth mode and AUTH port, URL blocker, password protection, programmable reset button
PPP authentication mechanisms	PAP, CHAP, MS-CHAP, and MS-CHAPv2
High availability / redundancy	VRRP (Virtual Router Redundancy Protocol), analog/GSM modem backup
Router	IPv4-, IPv6-, NetBIOS/IP multiprotokoll router, IPv4/IPv6 dual stack
Router virtualization	ARF (Advanced Routing and Forwarding) up to separate processing of 16 contexts
IPv4 services	HTTP and HTTPS server for configuration by web interface, DNS client, DNS server, DNS relay, DNS proxy, dynamic DNS client, DHCP client, DHCP relay and DHCP server including autodetection, NetBIOS/IP proxy, NTP client, SNTP server, policy-based routing, Bonjour-Proxy, RADIUS

LCOS 10.50

# LANCOM OAP-821

## Layer 3 features

IPv6 services	HTTP and HTTPS server for configuration by web interface, DHCPv6 client, DHCPv6 server, DHCPv6 relay, DNS client, DNS server, dynamic DNS client, NTP client, SNTP server, Bonjour-Proxy, RADIUS
Dynamic routing protocols	RIPv2
IPv4 protocols	DNS, HTTP, HTTPS, ICMP, NTP/SNTP, NetBIOS, PPPoE (server), RADIUS, RADSEC (secure RADIUS), RTP, SNMPv1,v2c,v3, TFTP, TACACS+, IGMPv3
IPv6 protocols	NDP, stateless address autoconfiguration (SLAAC), stateful address autoconfiguration (DHCPv6), router advertisements, ICMPv6, DHCPv6, DNS, HTTP, HTTPS, PPPoE, RADIUS, SMTP, NTP, Syslog, SNMPv1,v2c,v3, MLDv2, NPTv6 (NAT66)
WAN operating mode	VDSL, ADSL1, ADSL2 or ADSL2+ additional with external DSL modem at an ETH port
WAN protocols	PPPoE, Multi-PPPoE, ML-PPP, GRE, EoGRE, PPTP (PAC or PNS), L2TPv2 (LAC or LNS), L2TPv3 with Ethernet-Pseudowire, IPoE (using DHCP or no DHCP), RIP-1, RIP-2, VLAN, IPv6 over PPP (IPv6 and IPv4/IPv6 dual stack session), IP(v6)oE (autokonfiguration, DHCPv6 or static)
Tunneling protocols (IPv4/IPv6)	6to4, 6in4, 6rd (static and over DHCP), Dual Stack Lite (IPv4-in-IPv6-Tunnel), 464XLAT

## Interfaces

Ethernet port	1 x 10/100/1000BASE-T autosensing (RJ-45), PoE (Power over Ethernet)
External antenna connectors	Two N connectors

## Hardware

Power supply	Via Power over Ethernet, compliant with IEEE 802.3af
Environment	Temperature range -33°C to +70°C
Power consumption (max)	11 watt, incl. PoE-Injector
Housing	Robust metal housing, IP 66 protection rating, ready for wall and pole mounting, 3 LEDs for status display, please note: device must not be mounted in salt water environments without a suitable protective housing; Dimensions 255 x 250 x 80 mm (length x width x depth)

## Management and monitoring

Management	LANCOM Management Cloud, LANconfig, WEBconfig, WLAN controller, LANCOM Layer 2 management (emergency management)
Management functions	Alternative boot configuration, voluntary automatic updates for LCMS and LCOS, individual access and function rights up to 16 administrators, RADIUS and RADSEC user management, remote access (WAN or (W)LAN, access rights (read/write) adjustable separately), SSL, SSH, HTTPS, Telnet, TFTP, SNMP, HTTP, access rights via TACACS+, scripting, timed control of all parameters and actions through cron job
FirmSafe	Two stored firmware versions, incl. test mode for firmware updates

LCOS 10.50

# LANCOM OAP-821

## Management and monitoring

automatic firmware update	configurable automatic checking and installation of firmware updates
Monitoring	LANCOM Management Cloud, LANmonitor, WLANmonitor
Monitoring functions	Device SYSLOG, SNMPv1,v2c,v3 incl. SNMP-TRAPS, extensive LOG and TRACE options, PING and TRACEROUTE for checking connections, internal logging buffer for firewall events
Monitoring statistics	Extensive Ethernet, IP and DNS statistics; SYSLOG error counter, accounting information exportable via LANmonitor and SYSLOG
IPerf	IPerf is a tool for measurements of the bandwidth on IP networks (integrated client and server)
SLA-Monitor (ICMP)	Performance monitoring of connections
SD-WLAN	SD-WLAN – automatic WLAN configuration via the LANCOM Management Cloud
SD-LAN	SD-LAN – automatic LAN configuration via the LANCOM Management Cloud

## Declarations of conformity\*

CE	EN 60950-1, EN 301 489-1, EN 301 489-17
5 GHz WLAN	EN 301 893
2.4 GHz WLAN	EN 300 328
IPv6	IPv6 Ready Gold
Country of Origin	Made in Germany
*) Note	You will find all declarations of conformity in the products section of our website at <a href="http://www.lancom-systems.com">www.lancom-systems.com</a>

## Scope of delivery

Manual	Hardware Quick Reference (DE/EN), Installation Guide (DE/EN)
Cable	Water-resistant, UV-resistant Ethernet PoE cable with water-resistant screw connector, 15m, temperature range from -33°C to +70°C
Mounting Kit	Mounting kit for wall and pole mounting
Antennas	Two 3 dBi dipole antennas (Gain depends on frequency.)
Power supply unit	Via Power over Ethernet compliant with IEEE 802.3af, 1 x PoE Injector supplied

## Support

Warranty	3 years For details, please refer to the General Warranty Conditions at: <a href="http://www.lancom-systems.com/warranty-conditions">www.lancom-systems.com/warranty-conditions</a>
----------	--



LCOS 10.50

# LANCOM OAP-821

## Support

Software updates	Regular free updates as part of the LANCOM Software Lifecycle Managements ( <a href="http://www.lancom-systems.com/lifecycle">www.lancom-systems.com/lifecycle</a> )
Manufacturer support	Free technical manufacturer support as part of the LANCOM Software Lifecycle Management ( <a href="http://www.lancom-systems.com/lifecycle">www.lancom-systems.com/lifecycle</a> ).

## Software

Software Lifecycle Management	After discontinuation, the device is subject to the LANCOM Software Lifecycle Management. Details can be found at: <a href="http://www.lancom-systems.com/lifecycle">www.lancom-systems.com/lifecycle</a>
Anti-backdoor policy	Products from LANCOM are free of hidden access paths (backdoors) and other undesirable features for introducing, extracting or manipulating data. The trust seal "IT Security made in Germany" (ITSMIG) and certification by the German Federal Office for Information Security (BSI) confirm the trustworthiness and the outstanding level of security.

## Options

LANCOM Warranty Basic Option L	Option to extend the manufacturer's warranty from 3 to 5 years, item no. 10712
LANCOM Warranty Advanced Option L	Option to extend the manufacturer's warranty from 3 to 5 years and replacement of a defective device, item no. 10717
LANCOM Service Pack 24/7 L *	The LANCOM Service Pack 24/7 Emergency Support offers end customers direct manufacturer support with a guaranteed initial response time of max. 30 minutes in the event of massive operational disruptions. Additional extended service times for concerns outside of emergency support (Monday to Friday, 8 a.m. to 6 p.m.). It also includes advance replacement in the event of a hardware defect, including delivery of a replacement device on the next working day. The following terms are available: → 1 year: item no. 10232 → 3 years: item no. 10236 → 5 years: item no. 10240
LANCOM Service Pack 10/5 L *	The LANCOM Service Pack 10/5 offers end customers direct manufacturer support for ten hours on five working days with a maximum initial response time of four hours. It also includes advance replacement in the event of a hardware defect, including delivery of a replacement device on the next working day. The following terms are available: → 1 year: item no. 10248 → 3 years: item no. 10249 → 5 years: item no. 10250
LANCOM OAP VPN	Option for the extension of the LANCOM OAP-8xx and OAP-170xB series with IPSec VPN functionality, 5 active VPN channels enable the secure maintenance and management of OAPs, and the provision of confidential WLANs via a VPN connection to the company headquarters, item no. 61635
LANCOM Public Spot	Hotspot option for LANCOM products, versatile access (via voucher, e-mail, SMS), including a comfortable setup wizard, secure separation of guest access and internal network, item no. 60642
*) Note	Further details on LANCOM Service Packs are available at the following Internet address: <a href="http://www.lancom-systems.com/products/services-and-support">www.lancom-systems.com/products/services-and-support</a>

LCOS 10.50

# LANCOM OAP-821

## LANCOM Management Cloud

LANCOM LMC-A-1Y LMC License	LANCOM LMC-A-1Y License (1 Year), enables the management of one category A device for one year via the LANCOM Management Cloud, item no. 50100
LANCOM LMC-A-3Y LMC License	LANCOM LMC-A-3Y License (3 Years), enables the management of one category A device for three years via the LANCOM Management Cloud, item no. 50101
LANCOM LMC-A-5Y LMC License	LANCOM LMC-A-5Y License (5 Years), enables the management of one category A device for five years via the LANCOM Management Cloud, item no. 50102
LANCOM LMC-A-10Y LMC License	LANCOM LMC-A-10Y License (10 Years), enables the management of one category A device for ten years via the LANCOM Management Cloud, item no. 50132

## Accessories

LANCOM WLAN controllers	LANCOM WLC-4006+, item no. 62035 (EU), item no. 62036 (UK) and item no. 62037 (US), LANCOM WLC-1000, item no. 61783 (EU), LANCOM WLC Basic Option for Routers, item no. 61639
External antenna, outdoor use	AirLancer Extender O-D80g, item no. 61221, AirLancer Extender O-D60a, item no. 61222, AirLancer Extender O-D9a, item no. 61224
Antenna cable	AirLancer cable NJ-NP 3m, item no. 61230, AirLancer cable NJ-NP 6m, item no. 61231, AirLancer cable NJ-NP 9m, item no. 61232
Surge arrester (antenna cable)	AirLancer SN-ANT surge arrester (2.4 and 5 GHz), to be integrated between Access Point and antenna, item no. 61258
Surge arrester (antenna cable)	AirLancer Extender SA-5L surge arrester (2.4 and 5 GHz), to be integrated between Access Point and antenna, item no. 61553
Surge arrester (LAN cable)	AirLancer Extender SN-LAN surge arrester (LAN cable), item no. 61261
LAN cable (outdoor)	LANCOM OAP Ethernet cable (30 m), item no. 61347
Power over Ethernet Injector	1-port PoE injector with Gigabit support, integrated power supply, compatible with the standard IEEE 802.3af/at, item no. 61738 (EU) and 61739 (UK)
*) Note	The polarization diversity antennas require 2 cables and surge arrestors

LCOS 10.50

lancom-systems.com

# LANCOM OAP-821

---

**Item number(s)**

---

LANCOM OAP-821

61660

---

---

